



MAN OVERBOARD (MOB) - IKAROS



Transports
Canada



MED Certified

This distress signal is designed to be mounted vertically on the ship's bridge, with one on the port and one on the starboard side.

It should be attached behind or to the side of a lifebuoy at a minimum of five meters above the water line. When the lifebuoy is thrown overboard, the MOB is pulled with it and as it leaves its bracket, it automatically emits light and smoke to attract attention to the person in the water. On smaller vessels, it can be mounted on the wheelhouse bulkhead and launched manually.

The MOB light and smoke signal has a lithium battery and can be used as a day and night marker. It is approved globally and meets the latest SOLAS regulations.

- ▶ Attach to lifebuoy
- ▶ 2 hours light
- ▶ 15 minutes smoke
- ▶ Globally approved
- ▶ 60 meter drop test on water



Man overboard (MOB) light and smoke signal

	MOB MK IV light and smoke	MOB MK IV smoke marker
Performance	Light 2 cd > 2 hours	-
Smoke duration	> 15 min	> 15 min
Dimensions	200 x 500 mm	200 x 500 mm
Weight (including bracket)	approx. 5 kg	approx. 5 kg
Ref. no.	34 51 05	34 52 05
USCG no.	161.110/EC0575/MEDB000046Y (Light), 160.157/EC0575/MEDB000046X (Smoke)	
SOLAS MED B	MEDB000046Y (Light) MEDB000046X (Smoke)	



Aydıntepe Mah. Sahil Bulvarı Alize İş Merkezi Kat:2 No:102 Tuzla / İstanbul

sales@kuzey-marine.com

+90 216 266 72 85